UNCLASSIFIED

AD 273 650

Reproduced by the

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA



UNCLASSIFIED

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U.S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

27365

THE UNITED INTER

GRAPHS OF THE REAL AND IMAGINARY PARTS OF THE EFFECTIVE COLLISION FREQUENCY FOR WEAKLY IONIZED AIR

Paul Molmud

Space Technology Laboratories, Inc.

ONE SPACE PARK
REDONDO BEACH, CALIFORNIA

8625-6001-RU-000

Contract No. AF19(604)-8844

Scientific Report #1

January 1962

DASA MIPR 544-61

Prepared for

ELECTRONICS RESEARCH DIRECTORATE
AIR FORCE CAMBRIDGE RESEARCH LABORATORIES
OFFICE OF AEROSPACE RESEARCH
UNITED STATES AIR FORCE
BEDFORD, MASSACHUSETTS

N-62-2-6

GRAPHS OF THE REAL AND IMAGINARY PARTS OF THE EFFECTIVE COLLISION FREQUENCY FOR WEAKLY IONIZED AIR

Paul Molmud

Space Technology Laboratories, Inc.
One Space Park
Redondo Beach, California

8625-6001-RU-000

Contract No. AF19(604)-8844

Scientific Report #1

January 1962

DASA MIPR 544-61

Prepared for

Electronics Research Directorate
Air Force Cambridge Research Laboratories
Office of Aerospace Research
United States Air Force
Bedford, Massachusetts

"Requests for additional copies by Agencies of the Department of Defense, their contractors, and other Government agencies should be directed to the:

ARMED SERVICES YECHNICAL INFORMATION AGENCY ARLINGTON HALL STATION ARLINGTON 12, VIRGINIA

"All other persons and organisations should apply to the:

U.S. DEPARTMENT OF COMMENCE OFFICE OF TECHNICAL SERVICES WASHINGTON 25, D.C." Contract No. AF19(604)-8844

Prepared:

Paul Molmud

Theoretical Physics Department

Approved:

S. Altshuler

Manager

Theoretical Physics Department

Approved:

H. C. Corben

Director

Quantum Physics Laboratory

ABSTRACT

Graphs of the real and imaginary parts of the effective collision frequency for air are presented. The propagation constants for an E.M. wave propagating in ionized air with a static magnetic field are presented in terms of these effective collision frequencies. A numerical example illustrating the use of these graphs is worked out.

TABLE OF CONTENTS

A DD FRA	nty			_					
IV.	A NUMERICAL EXAMPLE		• •	• •		• •	•	•	
III.	THE PROPAGATION CONSTANTS .	• •	• •	• •			•	• •	. 3
II.	THE CONDUCTIVITY TENSOR	• •		• •	• •		•	•	. 2
I.	INTRODUCTION	• •	• •	• •	• •	• •	•	•	. 1

I. Introduction

In a previous paper it was shown that the use of the Langevin equation to describe the conductivity of a weakly ionized gas is incorrect unless the dissipative term g is interpreted as complex. Limiting forms of both the real and imaginary parts of g were given under either low or high pressure conditions. Analytical expressions for conductivity valid for all pressures were presented for several gases including air. Phelps has also presented the correct analytical expressions for the conductivity of air.

The Langevin equation reads as follows:

$$\frac{d\mathbf{v}}{dt} + \mathbf{g}\mathbf{v} = \frac{\mathbf{q}}{m} \mathbf{E}_{\mathbf{0}} \mathbf{e}^{\mathbf{i}\omega t}$$

where v is the average drift velocity of electrons in the gas, g is the dissipative term, often erroneously called the "collision frequency" and q = -e; m and E have their usual meanings. Equation (1) and its steady state solution:

(2)
$$v = \frac{1}{i\omega + g} \left(\frac{q}{m}\right) E_{o}e^{i\omega t}$$

are the starting points for many discussions on the conductivity and propagation constants of weakly ionized gases. 1,2,3

Our purpose in this paper is to present in graphical form the values of $g = g_r + ig_i$ for intermediate values of $\frac{\omega}{D}$ where $\mathcal V$ is the average collision frequency $g_r^{1,4}$. We call $g_r^{1,4}$ the "effective collision frequency" and $g_r^{1,4}$ and $g_r^{1,4}$ the real and imaginary parts respectively. We see that knowledge of their values enables us immediately to correct the previous analysis in (for example) references 2 and 3; for: The usual starting point is

(2†)
$$v = \frac{1}{i\omega + \gamma} \left(\frac{q}{m}\right) E_0 e^{i\omega t}$$

whereas the correct relationship is

(2")
$$v = \frac{1}{i(\omega + g_i) + g_r} \left(\frac{q}{m}\right) E_o e^{i\omega t}$$

Thus to correct the already available analyses whenever an expression for conductivity, $\delta\left(\omega,\mathcal{V}\right)$, occurs just replace ω by $\omega+g_{\underline{i}}$ and \mathcal{V} by $g_{\underline{r}}$ (i.e., $\delta\left(\omega+g_{\underline{i}},g_{\underline{r}}\right)$). The values of $g_{\underline{i}}$ and $g_{\underline{r}}$ are determined by the ratio $\frac{\omega}{\mathcal{V}}$. We give some examples of the application of this method below drawing heavily on the results of reference 1.

II. The Conductivity Tensor The conductivity tensor | | | | | | is given by

(4)
$$\| \mathbf{G} \| = \frac{\omega^{2}}{8\pi} \| \mathbf{L} + \mathbf{R} \quad \mathbf{i}(\mathbf{R} - \mathbf{L}) \quad \mathbf{0} \\ \mathbf{i}(\mathbf{L} + \mathbf{R}) \quad \mathbf{L} + \mathbf{R} \quad \mathbf{0} \\ \mathbf{0} \quad \mathbf{0} \quad \mathbf{2P} \|$$

where

(5)
$$P = \frac{1}{g_n + i(\omega + g_n)}$$

(6)
$$L = \frac{1}{g_{r}^{+} + i(\omega + \omega_{b} + g_{1}^{+})}$$

(7)
$$R = \frac{1}{g_{r}^{-} + i(\omega - \omega_{b}^{+} g_{i}^{-})}$$

where $\omega_b = \frac{q |H|}{mc} = \frac{eH}{mc}$ the cyclotron frequency and $\omega_p^2 = \frac{4mme^2}{m}$. g_T^{\pm} and g_1^{\pm} are obtained by looking up their values in the graphs (Figs. 1 and 2) under the appropriate value of $\frac{\omega \pm \omega_b}{\mathcal{V}}$. Thus should $|\omega| = |\omega_b|$, then in (7), $g_1^- = 2(\omega - \omega_b) = 0$ and $g_1^- = \mathcal{V}$; whereas in (6) g_T^+ could range anywhere from \mathcal{V} to $\frac{5}{3}\mathcal{V}$ and g_T^+ from 0 to $2(\omega + \omega_g)$ depending on the magnitude of $\frac{\omega + \omega_b}{\mathcal{V}}$.

III. The Propagation Constants

The propagation constants for an electromagnetic wave in a conducting gas in a magnetic field have been given already by Phelps⁶ in terms of the conductivity.

In the language of effective collision frequencies, we

* Alternatively
$$\omega P = \omega B \left(\frac{3\omega}{2y}\right) - i\omega D \left(\frac{3\omega}{2y}\right)$$
,
$$(\omega + \omega_b)L = (\omega + \omega_b) \left[B\left(\frac{3}{2}\frac{\omega + \omega_b}{y}\right) - iD\left(\frac{3}{2}\frac{\omega + \omega_b}{y}\right)\right]$$

$$(\omega - \omega_b)R = (\omega - \omega_b) \left[B\left(\frac{3}{2}\frac{\omega - \omega_b}{y}\right) - iD\left(\frac{3}{2}\frac{\omega - \omega_b}{y}\right)\right]$$

and wB and wB are graphed. See reference 5.

present the following propagation constants (paraphasing Phelps 6).

a) Propagation parallel to the magnetic field

(8)
$${\binom{K_o}{K_x}} = \frac{\omega}{c} \left\{ 1 - \frac{\omega_p^2}{\omega} {\binom{L}{R}} \right\}^{\frac{1}{2}} = \frac{\omega}{c} \left\{ 1 - \frac{\left[\omega_p^2 (\omega \pm \omega_b + g_1^{\pm}) + i\omega_p^2 g_r^{\pm}\right]}{\omega \left[(g_r^{\pm})^2 + (\omega \pm \omega_b + g_1^{\pm})^2\right]} \right\}^{\frac{1}{2}}$$

The wave associated with the + sign is the ordinary wave and is left circularly polarized about the direction of propagation. The minus sign is associated with the extraordinary wave which is right circularly polarized.

Writing K = μ - ik where μ is the real part of the refractive index and k is the absorption coefficient and assuming $\frac{\omega}{\omega(\omega-\omega_{k})}^{2}$

We obtain

(9)
$$\left\{ \begin{matrix} \mu_{o} \\ \mu_{x} \end{matrix} \right\} = \frac{\omega}{c} \left\{ 1 - \frac{\omega_{p}^{2}}{2\omega} \frac{(\omega \pm \omega_{b} + g_{1}^{\pm})}{\left[(\omega \pm \omega_{b} + g_{1}^{\pm})^{2} + (g_{r}^{\pm})^{2} \right]} \right\}$$

(10)
$$\begin{cases} k_o \\ k_x \end{cases} = \frac{\omega_p^2}{2c} \frac{g_r^{\pm}}{\left[(\omega \pm \omega_b + g_i^{\pm})^2 + (g_r^{\pm})^2 \right]}$$

b) Propagation perpendicular to the magnetic field

(11)
$$K_0 = \frac{\omega}{c} \left[1 - \frac{i\omega_p^2}{\omega} P \right]^{\frac{1}{2}} = \frac{\omega}{c} \left[1 - \frac{\omega_p^2}{\omega} \frac{\left[\omega + g_i + ig_r \right]}{\left(\omega + g_i \right)^2 + g_r^2} \right]^{\frac{1}{2}}$$

(12)
$$k_{x} = \frac{\omega}{c} \left\{ 1 + \frac{\omega_{p}^{2}(L+R) + 2 \frac{\omega_{p}^{4}}{i\omega} RL}{2i\omega + \omega_{p}^{2}(R+L)} \right\}^{\frac{1}{2}} *$$

^{*}The equivalent Equation (21) of Phelps appears to be in error.

When
$$\frac{\omega_{p}^{2}}{\omega^{2}} \ll 1$$
 then
$$\mu_{o} = \frac{\omega}{c} \left[1 - \frac{\omega_{p}^{2}}{2\omega} \frac{(\omega + g_{1})}{((\omega + g_{1})^{2} + (g_{r})^{2})} \right]$$

$$k_{o} = \frac{\omega_{p}^{2}}{2c} \frac{g_{r}}{((\omega + g_{1})^{2} + g_{r}^{2})}$$
Also when $\frac{\omega_{p}^{2}}{\omega (\omega - \omega_{b})} \ll 1$

$$\mu_{x} = \frac{\omega}{c} \left[1 - \frac{\omega_{p}^{2}}{4\omega} \frac{(\omega + \omega_{b} + g_{1}^{+})}{((\omega + \omega_{b} + g_{1}^{+})^{2} + (g_{r}^{+})^{2})} - \frac{\omega_{p}^{2}}{4\omega} \frac{(\omega - \omega_{b} + g_{1}^{-})}{((\omega - \omega_{b} + g_{1}^{-})^{2} + (g_{r}^{-})^{2})} \right]$$
(14)
$$k_{x} = \frac{\omega_{p}^{2}}{4c} \left[\frac{g_{r}^{+}}{(\omega + \omega_{b} + g_{1}^{+})^{2} + (g_{r}^{+})^{2}} + \frac{g_{r}^{-}}{(\omega - \omega_{b} + g_{1}^{-})^{2} + (g_{r}^{-})^{2}} \right]$$

IV. A Numerical Example

Let $\omega = 2\nu = 2\omega_{\rm b}$, (i.e., suppose we are propagating a wave of angular frequency ω is ionized air where according to Phelps' relationship $\left[\nu = 1.04 \times 10^8 \text{ p sec}^{-1}\right]$ the collision frequency is half that of the angular frequency). Then find the absorption coefficient for the extraordinary mode of a wave propagating perpendicular to the magnetic field (i.e., k_{χ} of Equation 14) assuming

$$\frac{\omega_{p}^{2}}{\omega(\omega-\omega_{b})} <<1.$$

Since

$$\frac{\omega + \omega_{b}}{V} = \frac{\omega(1 + \frac{1}{2})}{V} = 2 \times \frac{3}{2} = 3,$$

thus

$$g_{r}^{+} = 1.52 \nu$$
 , $g_{i}^{+} = .07(\omega + \omega_{b})$

and

$$\frac{\omega - \omega_b}{\mathcal{V}} = \frac{\omega(1 + \frac{1}{2})}{\mathcal{V}} = 2 \times \frac{1}{2} = 1,$$

then

and

$$g_i^- = .23 (\omega - \omega_b)$$
.

Then

$$k_{x} = \frac{\omega_{p}^{2}}{4c} \left[\frac{1.52 y}{(1.07)^{2} (\omega + \omega_{b})^{2} + (1.52)^{2} y^{2}} + \frac{1.31 y}{(1.23)^{2} (\omega - \omega_{b})^{2} + (1.31)^{2} y^{2}} \right]$$
$$= \frac{\omega_{p}^{2}}{4c} \left[\frac{1.52}{(1.07)^{2} \times 9 + (1.52)^{2}} + \frac{1.31}{(1.23)^{2} + (1.31)^{2}} \right] = .525 \frac{\omega_{p}^{2}}{4c y}$$

The conventional formulation would have

$$k_x = \frac{\omega_p^2}{4c} \left[\frac{y}{(\omega + \omega_b)^2 + v^2} + \frac{y}{(\omega - \omega_b)^2 + v^2} \right]$$

instead of (14), and substituting in the above values for ω , $\mathcal V$ and ω_h , we get

$$k_x = \frac{\omega_p^2}{4cV} \left[\frac{1}{9+1} + \frac{1}{1+1} \right] = \frac{\omega_p^2}{4cV}$$
 [.6]

Thus using the incorrect formulation we incur an error of 14%.

APPENDIX

The Propagation Constant for Arbitrary Direction of Propagation

Sen and Wyller⁷ have given the propagation constant for propagation in an arbitrary direction. We reproduce their formula in the language of the components of the conductivity tensor, equations (5), (6), (7).

A1)
$$K^2 = \frac{A + B \sin^2 \varphi \pm \sqrt{B^2 \sin^4 \varphi - C^2 \cos^2 \varphi}}{D + E \sin^2 \varphi}$$

Where ϕ is the angle between the magnetic field and the direction of propagation and

$$A = 2\varepsilon_1 (\varepsilon_1 + \varepsilon_3)$$

$$B = \varepsilon_3 (\varepsilon_1 + \varepsilon_3) + \varepsilon_2^2$$

$$C = 2\varepsilon_1 \varepsilon_2, D = 2\varepsilon_1, E = 2\varepsilon_3$$

and

$$\varepsilon_{1} = 1 - \frac{i\omega_{p}^{2}}{\omega} P$$

$$\varepsilon_{2} = \frac{1}{2} \frac{\omega_{p}^{2}}{\omega} [R - L]$$

$$\varepsilon_{3} = \frac{i\omega_{p}^{2}}{\omega} [P - \frac{1}{2} (L + R)]$$

FOOTNOTES

- 1. P. Molmud, Phys. Rev., 114, 29 (1959).
- 2. S. K. Mitra, "The Upper Atmosphere", (The Asiatic Society, Calcutta, 1952), 2nd ed.
- 3. J. A. Ratcliffe, "The Magneto-Ionic Theory and Its Application of the Ionosphere" (Cambridge U. Press, Cambridge, England, 1959).
- 4. A. V. Phelps, J. Ap. Phys., 31, No. 10, p. 1723, (1960). These expressions are exactly equivalent to those the author presented in reference 1. Phelps parameter $\frac{1}{3}$ is my $X = \frac{3\omega}{2V}$ and $\sqrt{}$ is the average collision frequency. For air $\sqrt{}$ is given by Phelps as: $\sqrt{} = 1.04 \times 10^8$ p sec⁻¹ where p is the pressure in mm. Hg.
- 5. g_r and g_i are computed from analytical expressions given in reference 1. See particularly Equations 4 and A3 and A4 in this reference where $\omega B = \frac{5}{2} \times C_{5/2}(X)$ and $\omega D = X^2 C_{3/2}(X)$. The latter two functions have been tabulated by Dingle, Arnt and Roy, Appl. Sci. Research 6B, 155, (1956). ωB and ωD may be found graphed in P. Molmud, "The Electrical Conductivity of Weakly Ionized Air" R. W., GM 47-78, 30 Sept. 1958, Phelps 4 function A2 and B2 are equivalent respectively to ΔB and ΔD where ΔC is either ω , $\omega + \omega_D$ or $\omega \omega_D$.
- 6. Phelps, Op. Cit., p. 1727, Eq. (16) thru (23). To translate his A's and B's to effective collision frequencies simply employ the following translations

$$A(\omega \pm \omega_b) \rightarrow \frac{g_r^{\pm} (\omega \pm \omega_b)}{(\omega \pm \omega_b + g_i^{\pm})^2 + (g_r^{\pm})^2}$$

$$B(\omega \pm \omega_b) \rightarrow \frac{(\omega \pm \omega_b + g_i^{\pm})(\omega \pm \omega_b)}{(\omega \pm \omega_b + g_i^{\pm})^2 + (g_r^{\pm})^2}$$

7. H. K. Sen and A. A. Wyller, Journal of Geophysical Research, Vol. 65, No. 12, Dec. 1960.




Figure 1




Figure 2